



VALMET AUTOMOTIVE

MODULAR POWER PACK, 48 V

UNIQUE COMBINATION OF
PERFORMANCE, DURABILITY AND
LIFETIME IN ONE COMPACT PACKAGE



FEATURES

DIRECT CELL-TO-PACK CONCEPT

- Optimized structure
- High packaging density

EXCEPTIONAL COOLING PERFORMANCE

- Advanced liquid cooling
- Maximized cell cycle life
- High continuous current capability

HIGH POWER DENSITY

- High peak power capability
- Fast charging compatibility

EFFICIENT USE OF AVAILABLE SPACE

- High level of integration
- System can be distributed on machine or vehicle level

DESIGNED FOR SAFETY CRITICAL APPLICATIONS

- Safety certified Battery Management System (BMS)
- Robust passive safety structure

DESIGNED FOR HARSH ENVIRONMENT

- Die-casted aluminum housing provides protection against external forces
- High Ingres Protection grade (IP6k9k)

THERMAL PROPAGATION PREVENTION

- Cells protected by aluminum structure
- Stable and safe LTO cell chemistry

EASY INTEGRATION

- System integration can be done without high voltage work requirement
- Scalable system up to 300 kWh
- CANOpen or J1939 communication

DEVELOPED AND DESIGNED
TO MEET HIGH RELIABILITY
REQUIREMENTS WITH LONG
HISTORY OF AUTOMOTIVE
EXPERTISE.

WWW.VALMET-AUTOMOTIVE.COM



STANDARDS COMPLIANCE

ECE R100 Battery safety

ECE R10 EMC

UN 38.3 Transport Safety

ISO 16750 Environmental conditions

Functional Safety

- IEC 61508 SIL 2
- ISO 13849 PL C
- IEC 62061 SIL 2

VA EV SYSTEMS INFO AND CONTACT INFO

SAMI NIKKINEN

Senior Sales Manager,
Off-highway / Truck&Bus
sami.nikkinen@valmet-automotive.com

Valmet Automotive EV Systems
valmet-automotive.com/electrifying



VALMET AUTOMOTIVE

ELECTRICAL DATA

Power Pack 48 V

CAPACITY	2.2 kWh
ENERGY	46 Ah (1C @ 25°C)
CELL CHEMISTRY	Lithium Titanite Oxide (LTO)
NOMINAL VOLTAGE	48.3 VDC
VOLTAGE MIN/MAX	38 V / 56 V
PEAK DISCHARGING POWER (10 s) SOC >90 %, @ 25 °C	20 kW
PEAK CHARGING POWER (10 s)	20 kW
CONTINUOUS POWER	10 kW
POWER CONSUMPTION IN STANDBY	1 W
CYCLE LIFE	>20,000 to 80 % initial capacity @ 25 °C, 3C/3C, SOC 10 % - 90%

Performance of high capacity 48 V system comprising multiple packs (n) in parallel can be up to nx respective parameters

MECHANICAL DATA

Power Pack 48 V

DIMENSIONS (LxWxH)	483 mm x 380 mm x 160 mm
TOTAL WEIGHT*	41 kg
OPERATING TEMPERATURE RANGE	-30 °C ... +55 °C
RECOMMENDED OPERATING TEMPERATURE	+5 °C ... +35 °C
PROTECTION CLASS	IP6k9k
COOLANT PRESSURE (MAX.)	3.5 bar

* Dry weight

Configurations and images exemplary. Values depend on SOC, SOH and temperature. Valmet Automotive reserves the right to amend our products & their specification at any time when technical changes and/or innovations are made. No liability for printing errors & omissions. © Valmet Automotive, version May 2022.

DEVELOPED AND DESIGNED
TO MEET HIGH RELIABILITY
REQUIREMENTS WITH LONG
HISTORY OF AUTOMOTIVE
EXPERTISE.

WWW.VALMET-AUTOMOTIVE.COM

